


[Home](#)
[Products](#)
[Our History](#)
[About Us](#)
[Contact Us](#)

PRODUCTS

1-800-394-0016



NuQuip® Model RV Series Relief Valves Pressures Up to 60,000 psi (4,137 bar)

The NuQuip® Model RV Series Relief Valve working pressure ranges from 5,000 psi (345 bar) to 60,000 psi (4,137 bar). The high flow capacity helps relieve system pressure to provide maximum protection for your equipment. The relief valve is designed to be in-field adjustable. Services include water and other liquids.

Contact [Airmo](#) for custom design options.



Product Features

	Specifications	Description
	Maximum Pressure:	Working pressures from 5,000 psi to 60,000 psi (345 bar to 4,137 bar)
	Temperature:	32° F to 120° F (0° C to 49° C)
	Services:	Water and other liquids
	Flow Capacity:	High relief flow with low pressure rise (in-field adjustable)
	Port Style:	MP or HP ports standard
	Seal Materials:	Multiple seal materials
	Actuation Option:	Air-piloted clamp and release
	Air Requirement:	80 - 100 psi (5.5 - 6.9 bar)
	Construction:	Precision-machined, heat-treated stainless steel
	Custom Options:	Custom designs considered



[NuQuip® Model RV Series Relief Valves.pdf](#)



[NuQuip® Product Line Card.pdf](#)



Contact Airmo for Your System and Tool Needs



© Copyright 2020, Airmo Inc. Pressure Technologies. All rights reserved.

[SITEMAP](#) | [Copyright Policy](#) | [Privacy Policy](#)